REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	INITIAL RELEASE OF DRAWING	5/29/2014	BS
2	ADD NOTE 3	8/15/2014	BS







NOTES:

⚠1 MATERIAL: ELASTOMER AND DUROMETER OF 40, 50, 60 OR 70 TO BE SPECIFIED.
2 ALL DIMENSIONS ARE REFERENCE.
3 AVAILABLE WITH THREADS OF 1/4-20 UNC X 1/2" AND M6 X 1.0 X 1/2".

QTY.	DESCRIPTION	PART NUMBER	MATERIAL OR NOTES	ITEM
AR	ELASTOMER	K46-4	⚠1	4
2	MK460-M6	MK460-M6		3
2	MK460	MK460		2
	K46	K46		1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KARMAN RUBBER. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KARMAN RUBBER IS PROHIBITED.

	SIGNATURE	DATE
DRAWN	B. SENECAL	05/29/2014
CHECK	S. BROWN	05/29/2014
ENGR	B. SENECAL	05/29/2014
QA		
STRESS		
APPR		

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
.X =
.XX = ± 0.031
.XXX =
ANGLES = ±1°
INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994

KARMAN RUBBER VIBRO-INSULATORS®
FOR CONTROLLING NOISE, SHOCK & VIBRATION

TITLE: K46 SERIES VIBRO-INSULATOR WWW.KARMAN.COM

SIZE	CAGE CODE	DWG. NO.	REV
B		K46	2

DO NOT SCALE DRAWING	SCALE: 2:1	WEIGHT: .50 OZ.	SHEET 1 OF 1