REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	INITIAL RELEASE OF DRAWING	12/17/2014	BS
2	ADD DIMENSIONS OF HOLES, WASHER THICKNESS AND BASE THICKNESS. REVISE NOTE 1 TO INCLUDE 30 DUROMETER ELASTOMER.	1/2/2015	BS









NOTES:

1. MATERIAL: ELASTOMER AND DUROMETER OF 30, 40, 50, 60 OR 70 TO BE SPECIFIED.
2. ALL DIMENSIONS ARE REFERENCE.
3. AVAILABLE WITH THREADS OF 3/8-16 UNC AND M8 X 1.25.

QTY.	DESCRIPTION	PART NUMBER	MATERIAL OR NOTES	ITEM
AR	ELASTOMER	K696-6	1	6
1	MK690W	MK690W		5
1	MK690I-M8	MK696I-M8		4
1	MK690I	MK690I		3
1	MK690B	MK690B		2
	K696	K696		1

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KARMAN RUBBER. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KARMAN RUBBER IS PROHIBITED.

	SIGNATURE	DATE
DRAWN	B. SENECAL	12/17/2014
CHECK	S. BROWN	12/17/2014
ENGR	B. SENECAL	12/17/2014
QA		
STRESS		
APPR		

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
.X =
.XX = ± 0.031
.XXX =
ANGLES = ±1°
INTERPRET GEOMETRIC TOLERANCING PER:
ASME Y14.5M-1994

KARMAN RUBBER VIBRO-INSULATORS®
FOR CONTROLLING NOISE, SHOCK & VIBRATION

TITLE: K696 SERIES VIBRO-INSULATOR WWW.KARMAN.COM

SIZE	CAGE CODE	DWG. NO.	REV
B		K696	2

DO NOT SCALE DRAWING	SCALE: 1:1	WEIGHT: 6.3 OZ.	SHEET 1 OF 1