



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	INITIAL RELEASE OF DRAWING	5/28/2014	BS
2	ADD ITEM 3 AND NOTE 3	8/15/2014	BS

NOTES:

- 1 MATERIAL: ELASTOMER AND DUROMETER OF 40, 50, 60 OR 70 TO BE SPECIFIED.
- 2 ALL DIMENSIONS ARE REFERENCE.
- 3 AVAILABLE WITH THREADS OF 8-32 UNC X 1/2" AND M4 X .7 X 1/2".

AR	ELASTOMER	K806-3	1	4
2	MK800-M4	MK800-M4		3
2	MK800	MK800		2
	K806	K806		1
QTY.	DESCRIPTION	PART NUMBER	MATERIAL OR NOTES	ITEM

PROPRIETARY AND CONFIDENTIAL <small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KARMAN RUBBER. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KARMAN RUBBER IS PROHIBITED.</small>	SIGNATURE		DATE	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: .X = .XX = ± 0.031 .XXX = ANGLES = ±1° INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994
	DRAWN	B. SENECAL	05/28/2014	
	CHECK	S. BROWN	05/28/2014	
	ENGR	B. SENECAL	05/28/2014	
	QA			
	STRESS			
	APPR			

KARMAN RUBBER
VIBRO-INSULATORS®
FOR CONTROLLING NOISE, SHOCK & VIBRATION

SIZE	CAGE CODE
B	
DO NOT SCALE DRAWING	

TITLE: K806 SERIES VIBRO-INSULATOR WWW.KARMAN.COM			
DWG. NO. K806		REV 2	
SCALE: 2:1	WEIGHT: .20 OZ.	SHEET 1 OF 1	