REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	INITIAL RELEASE OF DRAWING	10/10/2014	BS
2	REVISE DIMENSION TABLE	12/23/2014	BS
3	REVISE DIMENSION TABLE	1/20/2015	BS
4	ADD DIMINSIONS TO INSTALLED VIEW AND CORRESPONDING VALUES IN DIMENSION TABLE.	2/12/2015	BS



INSTALLED VIEW
AXIAL LOAD DIRECTION



PART NO.	A	B	C	D	E	F	G	H	R	S	T
K20-0	1.09	0.400	0.81	0.500	0.19	0.70	1.25	1.12	0.06	0.78	0.25
K20-1	1.09	0.400	0.81	0.690	0.19	0.82	1.25	1.12	0.06	0.78	0.31
K20-2	2.00	0.640	1.35	1.690	0.53	2.00	2.25	2.00	0.06	1.30	0.75
K20-3	2.00	0.640	1.35	1.810	0.53	2.10	2.25	2.00	0.06	1.30	1.00
K20-4	1.93	0.530	1.31	1.310	0.50	1.56	2.25	2.00	0.06	1.26	0.63
K20-5	2.00	0.530	1.35	1.375	0.53	1.64	2.25	2.00	0.06	1.30	0.63
K20-6	2.48	0.630	1.49	0.945	0.61	1.18	2.88	2.25	0.06	1.43	0.31
K20-7	1.75	0.530	1.12	1.000	0.38	1.11	2.00	1.50	0.06	1.06	0.38
K20-8	2.37	0.640	1.50	1.500	0.70	2.13	2.75	2.50	0.06	1.44	0.63
K20-9	3.00	0.640	1.99	2.000	0.825	2.23	3.50	2.50	0.06	1.91	0.94
K20-11	1.09	0.400	0.81	0.500	0.38	0.80	1.25	1.12	0.03	0.78	0.12
K20-12	0.92	0.344	0.69	0.400	0.134	0.50	1.12	1.10	0.03	0.66	0.36
K20-13	1.09	0.400	0.81	0.620	0.19	1.02	1.25	1.12	0.03	0.78	0.43

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KARMAN RUBBER. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KARMAN RUBBER IS PROHIBITED.

	SIGNATURE	DATE
DRAWN	B. SENECAL	10/10/2014
CHECK	S. BROWN	10/10/2014
ENGR	B. SENECAL	10/10/2014
QA		
STRESS		
APPR		

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES:
.X =
.XX = ± 0.031
.XXX =
ANGLES = ±1°
INTERPRET GEOMETRIC TOLERANCING PER:
ASME Y14.5M-1994

KARMAN RUBBER VIBRO-INSULATORS®
FOR CONTROLLING NOISE, SHOCK & VIBRATION

TITLE: K20 SERIES VIBRO-INSULATOR WWW.KARMAN.COM

SIZE	CAGE CODE	DWG. NO.	REV
B		K20	4

DO NOT SCALE DRAWING	SCALE: 2:1	WEIGHT: N/A	SHEET 1 OF 1